

BLANK PAGE



Indian Standard

RECORDED CHARACTERISTIC FOR MAGNETIC SOUND ON FULL-COAT 16 mm MOTION-PICTURE FILM

UDC 778'534'455: 771'534'352

© Copyright 1987

BUREAU OF INDIAN STANDARDS

MANAK BHAYAN, 9 BAHADUR SHAH ZAFAR MARG

NEW DELHI 110002

IS: 11932 - 1986

Indian Standard

RECORDED CHARACTERISTIC FOR MAGNETIC SOUND ON FULL-COAT 16 mm MOTION-PICTURE FILM

Cinematographic Equipment Sectional Committee, ETDC 47

Chairman

SHRI B. A. MISTRY 15. Parsee Panchayet Road, Ministry Apartments, Bombay

Members

Representing

SHRI S. N. AGARWAL

Cinecita Pvt Ltd, Bombay

SHRI S. P. AGARWAL (Alternate) SHRI R. S. ARORA

Directorate General of Supplies and Disposals. New Delhi

SHRI D. L. TALWAR (Alternate)

SHRI S. C. BATRA

Directorate of Technical Development and Production (Air) Ministry of Defence.

New Delhi SHRI R. P. AGARWAL (Alternate)

SHRI N. P. BHATTACHARYA

National Council of Educational Research and Training, New Delhi

SHRI BHUPAN GHOSH

Cine Mechanical Works, Calcutta

SHRI MANNA LADIA (Alternate) Cine Sales Corporation, Delhi

SHRI Y. R. CHAUHAN

SHRI R. S. CHAUHAN (Alternate)

SHRI B. C. MUKHERJEE

National Test House, Calcutta Photophone Pyt Ltd. Bombay

SHRI M. C. MANI SHRI A. B. KUCHERIA (Alternate)

SHRI JAL P. MISTRY

International Talkie Equipment Co Pvt Ltd. Bombay

SHRI DIPAK B. ADALJA (Alternate)

SHRI MOHANIEET SINGH

Directorate General of Technical Development.

SHRI N. N. NARAYANA RAO

New Delhi Ministry of Defence (DGI), New Delhi

SHRI D. R. DHIMAN (Alternate)

SHRI S. B. THAKUR

Photophone Industries India Ltd. Goa

SHRI K. K. KOUL (Alternate)

(Continued on page 2)

@ Copyright 1987

BUREAU OF INDIAN STANDARDS

This publication is protected under the Indian Copyright Act (XIV of 1957) and reproduction in whole or in part by any means except with written permission of the publisher shall be deemed to be an infringement of copyright under the said Act.

IS: 11932 - 1986

(Continued from page 1)

Members	Representing
SHRI K. RAJGOPAL CHETTY	Devi Cine Projectors Manufacturing Co, Madras
SHRI K. M. GNENAPRAGASAM (Alternate)
SHRI RAM PRASAD	National Physical Laboratory (Optics Division) (CSIR), New Delhi
SHRI SATISH KUMAR	Film and T. V. Institute of India, Ministry of Information and Broadcasting, Pune
SHRI P. V. K. REDDI (Alternate	?)
Dr S. P. Singhal	National Physical Laboratory (Acoustic Division) (CSIR), New Delhi
Shri G. Sinha	Hindustan Photo Films Manufacturing Co, Ootacamund
SHRI A. R. MURALI (Alternate)
SHRI S. S. VOHRA	Film Division, Ministry of Information and Broadcasting, Bombay
SHRI S. P. SACHDEV, Director (Elec tech)	Director General, BIS (Ex-officio Member)

Secretary

SHRI B. K. MAHATA Joint Director (Elec tech), BIS

Indian Standard

RECORDED CHARACTERISTIC FOR MAGNETIC SOUND ON FULL-COAT 16 mm MOTION-PICTURE FILM

0. FOREWORD

- 0.1 This Indian Standard was adopted by the Indian Standards Institution on 26 November 1986, after the draft finalized by the Cinematographic Equipment Sectional Committee had been approved by the Electrotechnical Division Council.
- 0.2 While preparing this standard, assistance was derived from ISO 1188-1984 'Cinematography Recorded characteristic for magnetic sound on full-coat 16 mm motion-picture film Specifications', issued by the International Organization for Standardization (ISO).
- 0.3 For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated, expressing the result of a test or analysis, shall be rounded off in accordance with IS: 2-1960*. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

1. SCOPE

1.1 This standard specifies the recorded characteristic for magnetic sound records on 16 mm full-coat perforated magnetic film when used at the nominal speed of 24 frames (183 mm) per second, or 25 frames (190.5 mm) per second.

2. RECORDED CHARACTERISTIC

2.1 With constant sine-wave signal applied to the input of the recording system, the nominal characteristic in effective values of the short-circuit magnetic flux versus frequency shall fall with increasing frequency in conformity with the impedance of a parallel combination of a capacitance and a resistance having a time constant $t = 70 \,\mu\text{s}$.

^{*}Rules for rounding off numerical values (revised).

IS: 11932 - 1986

2.2 The curve defined above is represented by

$$N = -10 \log_{10} (1 + 4\pi^2 f^2 t^2)$$

where

N = the recorded characteristic in decibels;

f = the frequency in hertz; and

t = the time constant in seconds.

2.3 Numerical values are given in Table 1.

TABLE 1 NUMERICAL VALUES OF THE RECORDED CHARACTERISTICS

Frequency	N	
Hz	db	
40	0.13	
50	0.13	
63	0.13	
80	0.12	
100	0.12	
125	0.12	
160	0.11	
200	0.10	
250	0.08	
315	0.05	
400	0.00	
500	- 0·07	
630	− 0·19	
800	 0·37	
1 000	— 0 ·64	
1 250	- 1·01	
1 600	— 1·61	
2 000	- 2.36	
2 500	— 3·31	
3 150	- 4 ⋅52	
4 000	− 5 •99	
5 000	− 7·53	
6 300	- 9· 2 5	
8 000	-11:13	
10 000	-12·9 5	
12 500	—14·81	
16 000	— 16·90	

Note — Numerical values of the recorded characteristics normalized to 400 Hz.

3. TOLERANCES

3.1 Magnetic sound records on films shall be recorded to the characteristic specified in 2 within the tolerances given in the Fig. 1.




Fig. 1 Tolerances on Recorded Level on 16 mm Film

INTERNATIONAL SYSTEM OF UNITS (SI UNITS)

Base Units

Quantity	Unit	Symbol
Length	metre	m
Mass ·	kilogram	kg
Time	second	S
Electric current	ampere	A
Thermodynamic temperature	kelvin	K
Luminous intensity	candela	cd
Amount of substance	mole	mol

Supplementary Uuits

Quantity	Unit	Symbol
Plane angle	radian	rad
Solid angle	steradian	sr

Derived Units

Quantity	Unit	Symbo l	Definition
Force	newton	N	$1 N = 1 kg,m/s^2$
Energy	joule	J	1 J = 1 N.m
Power	watt	W	1 W = 1 J/s
Flux	weber	Wb	1 Wb = 1 V.s
Flux density	tesla	T	$1 T = 1 Wb/m^2$
Frequency	hertz	Hz	$1 \text{ Hz} = 1 \text{ c/s(s}^{-1})$
Electric conductance	siemens	S	1 S = 1 A/V
Electromotive force	volt	V	1 V = 1 W/A
Pressure, stress	pascal	Pa	$1 Pa = 1 N/m^2$